



Go straight to the source for Fuel Contamination Removal.

Stop the problem where it starts — install a Fleetguard Bulk Fuel Filter



ON SITE TANK
Clear Bowl Fuel Filter



AT THE BOWSER
*High Flow Fuel Filter
Water Separator*



BULK FUEL STORAGE

Stop the problem where it starts – install a Fleetguard Bulk Fuel Filter!

FS1285

Unique fuel island designed fuel filter/water separator using high efficiency water absorbing media. The filter is capable of high flow rate up to 152 litres per minute, and has the ability to remove similar size contamination at an efficiency commonly seen on the engine itself.

Filter life is determined by the noticeable drop in flow at the nozzle. Whilst the unit is capable of functioning in a suction situation it is recommended to install wherever possible down stream of the pump thereby avoiding possible pump cavitation.

FS 1285 FILTER DIMENSIONS

Height	287mm
OD	128mm

HH6973 HEAD

1⁵/₈" x 12" SAE



3307454S

Ideal for farm, industrial, construction and mining.

This bulk tank fuel filter assembly provides filtration at 19 litres per minute with little as two feet of head.

The unit comes complete with remote mount head (ports 1" npt) and clear see through bowl with petcock for drainage of sediment and water.

■ *Filter element FF246 should be ordered separately.*
FF246 – Replacement screw-in element.

For more information, contact your nearest stockist or phone Fleetguard Customer Assistance



Fleetguard Australia

31 Garden Street, Kilsyth,
 Victoria 3137, Australia
 Tel: (03) 9721 9100 or 1800 032 037
 Fax: (03) 9721 9147 or 1800 032 036
 Web Site : www.fleetguard.com
 E-mail: fleetassist@fleetguard.com

Fleetguard New Zealand

Tel: 0800 448 363
 Fax: 0800 448 367

Your Fleetguard Stockist: