

Cummins Filtration Chemwatch: 5268-60 Version No: 7.1.1. Safety Data Sheet according to HSNO Regulations Chemwatch Hazard Alert Code: 1

Issue Date: **04/03/2019** Print Date: **05/03/2019** S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	PG Platinum (Australia)		
Synonyms	Product Codes: CC36087, CC36086, CC36085, CC36084, CC36083, CC36082		
Other means of identification	Not Available		
Relevant identified uses of the substance or mixture and uses advised against			

Relevant identified uses of the substance of mixture and uses advised aga

Relevant identified uses Coolant.

Details of the supplier of the safety data sheet

Registered company name	Cummins Filtration
Address	31 Garden Street Kilsyth VIC 3137 Australia
Telephone	+61 3 9721 9100
Fax	+61 3 9721 9148
Website	Not Available
Email	Not Available

Emergency telephone number

Association / Organisation	Not Available	CHEMWATCH EMERGENCY RESPONSE			
Emergency telephone numbers	+61 3 9573 3112	+64 800 700 112			
Other emergency telephone numbers	+61 3 9573 3112	+61 2 9186 1132			

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

P337+P313

If eye irritation persists: Get medical advice/attention.

Classification ^[2]	Acute Toxicity (Oral) Category 4, Eye Irritation Category 2A, Acute Vertebrate Hazard Category 3
Legend:	1. Classified by Chernwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Gazetted by EPA New Zealand	6.1D (All), 6.1D (oral), 6.4A, 9.3C
Label elements	
Hazard pictogram(s)	
SIGNAL WORD	WARNING
Hazard statement(s)	
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H433	Harmful to terrestrial vertebrates.
Precautionary statement(s) P	revention
P273	Avoid release to the environment.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statement(s) R	esponse
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

 P301+P312
 IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.

 P330
 Rinse mouth.

Precautionary statement(s) Storage
Not Applicable
Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
57-55-6	30-60	propylene glycol
Not Available	1-10	Ingredients determined not to be hazardous
7732-18-5	30-60	water

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

• Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.

Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.

Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Propylene glycol is primarily a CNS depressant in large doses and may cause hypoglycaemia, lactic acidosis and seizures.

- The usual measures are supportive care and decontamination (Ipecac/ lavage/ activated charcoal/ cathartics), within 2 hours of exposure should suffice.
- ▶ Check the anion gap, arterial pH, renal function and glucose levels.

Ellenhorn and Barceloux: Medical Toxicology

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

In foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire.

	 Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area.
	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers.
Fire/Explosion Hazard	Decomposes on heating and produces toxic fumes of: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling • DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Safe handling Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. Store in original containers. Keep containers securely sealed. Other information No smoking, naked lights or ignition sources. ۲ Store in a cool, dry, well-ventilated area. Conditions for safe storage, including any incompatibilities Polyethylene or polypropylene container. Suitable container Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. Storage incompatibility • Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Not Available

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

water

Source	Ingredient	Material name	τw	A	STEL	Peak	Σ.	Notes
New Zealand Workplace Exposure Standards (WES)	propylene glycol	Propane-1,2-diol: Particulates only	10 mg/m3		Not Available	Not Available		Not Available
New Zealand Workplace Exposure Standards (WES)	propylene glycol	Propane-1,2-diol: Vapour and particulates	150 ppm / 474 mg/m3		Not Available Not Availab		Available	Not Available
EMERGENCY LIMITS	EMERGENCY LIMITS							
Ingredient Material name				-1	TEEL-2		TEEL-3	
propylene glycol	Polypropylene glyco	Polypropylene glycols		g/m3	330 mg/m3		2,000 mg/m3	
propylene glycol	Propylene glycol; (1,2-Propanediol)		30 mg/m3 1		1,300 mg/m3		7,900 mg/m3	
Ingredient				Kevisea IDLH				
propylene glycol	Not Available			Not Available				

Not Available

exposure controls	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	Overalls. P.V.C. apron. Barrier cream.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

PG Platinum (Australia)

Material	CPI
BUTYL	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final

selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear red liquid with a sweet odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	A-AUS / Class 1 P2	-	A-PAPR-AUS / Class 1 P2
up to 25 x ES	Air-line*	A-2 P2	A-PAPR-2 P2
up to 50 x ES	-	A-3 P2	-
50+ x ES	-	Air-line**	-

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7.5-9	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce respiratory irritation (as classified by E fumes or aerosols, especially for prolonged periods, may produce respiratory Inhalation of vapours may cause drowsiness and dizziness. This may be acco co-ordination, and vertigo. Inhalation of vapours or aerosols (mists, fumes), generated by the material du individual. Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drow and behavioural changes. Secondary respiratory depression and failure, as w Inhalation hazard is increased at higher temperatures.	C Directives using animal models). Nevertheless inhalation of vapours, discomfort and occasionally, distress. mpanied by sleepiness, reduced alertness, loss of reflexes, lack of ring the course of normal handling, may be damaging to the health of the vsiness, muscle weakness and delirium, central depression, coma, seizures ell as low blood pressure and irregular heart rhythms, may follow.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. If swallowed, the toxic effects of glycols (dihydric alcohols) are similar to those of alcohol, with depression of the central nervous system, nausea, vomiting, and degenerative changes in the liver and kidney. Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation. Excessive repeated ingestions may cause hypoglycaemia (low levels of glucose in the blood stream) among susceptible individuals; this may result in muscular weakness, incoordination and mental confusion. Very high doses given during feeding studies to rats and dogs produce central nervous system depression (although one-third of that produced by ethanol), haemolysis and insignificant kidney changes. Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion. delirium and coma.	
Skin Contact	There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. A single prolonged exposure is not likely to result in the material causing harm. However, when applied in large quantities to damaged skin as a topical preparation or by contact with clothing accidentally contaminated by the material, there may be the potential to absorb the material in harmful amounts. Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.	
Eye	Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).	
Chronic	There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population. Propylene glycol is thought to be sensitizing following the regular use of topical creams by eczema patients. Testing in humans showed that 16% of exposed individuals, irritation occurred, with 12.5% showing toxic or allergic reactions. The reaction responses reached their maximum on the second day or later. Reactions were seasonal in nature, with a maximum in winter.	
PG Platinum (Austrolia)	TOXICITY	IRRITATION
r o Flathum (Australia)	Not Available	Not Available

	TOXICITY	IRRITATION
propylene glycol	Dermal (rabbit) LD50: 11890 mg/kg ^[2]	Eye (rabbit): 100 mg - mild
	Inhalation (rat) LC50: >44.9 mg//4H ^[2]	Eye (rabbit): 500 mg/24h - mild
	Oral (rat) LD50: 20000 mg/kg ^[2]	Skin(human):104 mg/3d Intermit Mod
		Skin(human):500 mg/7days mild
water	TOXICITY	IRRITATION
	Oral (rat) LD50: >90000 mg/kg ^[2]	Not Available
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity data extracted from RTECS - Register of Toxic Effect of chemical Substances 	2.* Value obtained from manufacturer's SDS. Unless otherwise specified

PROPYLENE GLYCOL	PROPYLENE GLYCOL The acute oral toxicity of propylene glycol is very low; large amounts are needed to cause perceptible health damage in humans. Serious toxicity generally occurs only at blood concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time; this is nearly impossible with consuming foods or supplements which contain 1g/kg of PG at most. Poisonings are usually due to injection through a vein or accidental swallowing of large amounts by children. The potential for long-term oral toxicity is also low. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
WATER	R No significant acute toxicological data identified in literature search.		
Acute Toxicity	✓	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
Legend: X – Data either not available or does not fill the criteria for classification			

```
    Data available to make classification
```

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

PG Platinum (Australia)	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>10-mg/L	2
propylene glycol	EC50	48	Crustacea	43-500mg/L	2
	EC50	96	Algae or other aquatic plants	19-mg/L	2
	NOEC	168	Fish	11-530mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
water	LC50	96	Fish	897.520mg/L	3
			Alexa as ather an ether	0700.074	

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
propylene glycol	LOW (BCF = 1)
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)

water

LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	 Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Hazard Class

Marine Pollutant	NO Not Applicable
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance can be managed under the controls specified in the Transfer Notice or alternatively it may be managed using the conditions specified in an applicable Group Standard.

HSR Number	Group Standard		
HSR006574	Not Available		
PROPYLENE GLYCOL(57-55-6) IS	FOUND ON THE FOLLOWING REGULATORY LISTS		
GESAMP/EHS Composite List - GESAMP Hazard Profiles		IMO F	IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety
IMO IBC Code Chapter 17: Summary of minimum requirements		conta	
IMO IBC Code Chapter 18: List of products to which the Code does not apply		hazar	ds
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances		New 2 Cherr	Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of icals
		New 2 Chem	Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of nicals - Classification Data
		New	Zealand Inventory of Chemicals (NZIoC)
		New	Zealand Workplace Exposure Standards (WES)
WATER(7732-18-5) IS FOUND ON	THE FOLLOWING REGULATORY LISTS		
IMO IBC Code Chapter 18: List of products to which the Code does not apply		New	Zealand Inventory of Chemicals (NZIoC)
Hazardous Substance Locati	on		
Subject to the Health and Safety at W	/ork (Hazardous Substances) Regulations 2017.		
Hazard Class	Quantity beyond which controls apply for closed		Quantity beyond which controls apply when use occurring in open

	containers	containers	
Not Applicable	Not Applicable	Not Applicable	

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance Quantities	<i>!</i> S
Not Applicable Not Applic	cable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AICS	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Canada - DSL	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Canada - NDSL	No (propylene glycol; water; Ingredients determined not to be hazardous) Non-disclosed ingredients	
China - IECSC	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Europe - EINEC / ELINCS / NLP	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Japan - ENCS	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Korea - KECI	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
New Zealand - NZIoC	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Philippines - PICCS	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
USA - TSCA	No (Ingredients determined not to be hazardous) Non-disclosed ingredients	
Legend:	Yes = All ingredients are on the inventory No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Revision Date	04/03/2019
Initial Date	28/08/2017

SDS Version Summary

Version	Issue Date	Sections Updated
4.1.1.1	07/09/2017	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Appearance, Chronic Health, Classification, Disposal, First Aid (eye), Ingredients, Personal Protection (Respirator), Physical Properties, Storage (storage incompatibility), Storage (storage requirement), Name
7.1.1.1	04/03/2019	Ingredients, Storage (storage incompatibility)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level COTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.